



51323

FORD BRONCO
FORD ECONOLINE
FORD EXCURSION
FORD EXPEDITION
FORD EXPLORER
FORD F-SERIES
FORD WINDSTAR
LAND ROVER RANGEROVER
LINCOLN MARK LT
LINCOLN NAVIGATOR
MERCURY MOUNTAINEER

ELECTRIC BRAKE CONTROL
ADAPTER HARNESS



MUST READ FIRST!

All steps must be followed to ensure correct function of the harness. To verify proper installation once installed, test by connecting a brake controller and properly wired trailer.

3/9/2011

INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813

English

1. Locate the vehicle's electric brake control harness. The harness will be located under the dash near the center console on most vehicles. The harness for the Ford Full Size Van is located underneath and left of the steering column. There will be a 6-pin connector that mates with the one on the adapter at the end of the harness. Verify that there is battery power supplied to the connector by carefully probing the connector with a test light. This can also be accomplished by following the wires to their source, ensuring they do not dead end without connections behind the instrument panel. For vehicle's with power supplied at this connector, proceed to Step 3. Note: Some older vehicles will have a 4 pin connector in place of the 6-pin. Some Ford Windstar models are not equipped with a brake control connector.

2. For vehicles with no power to the electric brake control connector: Using an electric brake control wiring kit, route all wires as described in the wiring kit installation instructions. Cut the vehicle connector's battery feed wire, allowing enough wire remaining to connect the battery wire from the brake control wiring kit using the butt connector supplied. Cut the vehicle connector's trailer brake wire, allowing enough wire remaining to connect the trailer brake wire from the wiring kit using the supplied butt connector.

3. Plug the brake control adapter into the vehicle's electric brake control connector.

4. Plug the remaining connector into your Curt brake controller.

5. Complete the installation per the brake control installation instructions and mount the unit as directed. Perform test procedures as instructed.