



Double Lock QuickGoose2 Application Guide

Warning: On two wheel drive trucks a clearance check must be performed when truck is loaded and unloaded to verify the inverted ball will not interfere with the top of the differential.

600 Series Installation Kits (Rated to vehicles Max Gross Weight Rating)

Make/Model	Style	Years From	Years To	Double-Lock Hitch#	Quick Goose 2 Hitch#	Under-Bed Folding Ball Gooseneck Hitch #	Rail Kit#	Notes	Double-Lock Hitch/Rail Kit#
CHEVROLET/GMC									
1500 & 2500LD Silverado/Sierra	New Body	2007	2016	60615	n/a	n/a	60632	Z	60711
	Classic Body	1999	2007	60607	60630	61652	60652	Z	60712
2500HD & 3500 Silverado/Sierra		2011	2016	60607	n/a	n/a	60604	Z	60710
		2001	2010	60607	60630	61652	60652	Z,4	60712
2500 & 3500 Full Size Pickups	Old Body Excluding 34" Frame (O.D.)	1999	2000	60607	60630	61652	60631	Z	60713
1988	1998	60607	60630	61652	60631	Z	60713		
DODGE/RAM									
Ram 1500	Excluding Air Suspension	2009	2010	60607	n/a	n/a	60657	Z	60730
		2002	2008	60607	60640	n/a	60659	Z,1,2	60733
		1994	2001	60607	60640	n/a	60635	Z	60734
Ram 2500		2003	2010	60607	60640	n/a	60661	Z,1,2,6	60732
		2003	2010	60607	60640	n/a	60659	Z,1,2,6	60733
		1994	2002	60607	60640	n/a	60635	Z,6	60734
Ram 3500		2003	2010	60607	60640	n/a	60661	Z,1,2,6	60732
		2003	2010	60607	60640	n/a	60659	Z,1,2,6	60733
		1994	2002	60607	60640	n/a	60635	Z,6	60734
FORD									
F-150		2015	2016	60607	n/a	n/a	60649		n/a
		2004	2014	60607	60630	61652	60641	Z	60721
		1997	2003	60607	60630	61652	60637	Z	60722
		1980	1996	60607	60630	61652	60636	Z,1	60723
		2004	2004	60607	60630	61652	60637	Z	60722
F-250	New Body	1997	2003	60607	60630	61652	60637	Z	60722
	Old Body	1980	1998	60607	60630	61652	60636		60723
F-250 & F-350 Super Duty		2011	2016	60607	60630	61652	60644	Z,3	60720
		1999	2010	60607	60640	n/a	60644	Z,3	60720
		1999	2010	60607	60640	n/a	60643*	Z,3	n/a
F-350	Excluding Overload Springs	1980	1998	60607	60630	61652	60636	Z	60723
		1980	1998	60607	60630	61652	60636		60723
F-450 Super Duty	Excluding Cab & Chassis	2008	2012	60607	60640	n/a	60644	Z,3	60720
		2008	2010	60607	60640	n/a	60643*	Z,3	n/a
NISSAN									
Titan		2004	2015	60620	n/a	n/a	60664	Z,1	60740
RAM									
1500	Air Suspension	2013	2015	60607	n/a	n/a	60658	Z	60731
	Excluding Air Suspension	2011	2016	60607	n/a	n/a	60657	Z	60730
2500		2011	2013	60607	60640	n/a	60661	Z,1,2,6	60732
		2011	2012	60607	60640	n/a	60659	Z,1,2,6	60733
3500		2011	2012	60607	60640	n/a	60661	Z,1,2,6	60732
		2011	2012	60607	60640	n/a	60659	Z,1,2,6	60733
TOYOTA									
Tundra	6.5' Bed	2007	2016	60607	n/a	n/a	60667	Z,5	60751
		2000	2006	60625	n/a	n/a	60665	Z,6	60750

*While Supplies Last

600 Series Footnotes:

- 1 = Passenger side wheel well must be notched for frame rail access
- 2 = Parking brake cable bracket may require relocation
- 3 = Exhaust may have to be permanently lowered on 05 & newer models.
- 4 = Vacuum canister requires relocation (kit included)
- 5 = Ball cannot be turned over, brake lines must be cable tied (ties included)
- 6 = Do not invert ball with heavy loads on 2 wheel drive models
- Z = No frame drilling required

All Models: Brake, fuel, and electrical lines may need to be loosened or repositioned. Heat shield requires modification or removal